



## Ceramic Application

### TITANIUM DIOXIDE

GRADE	APPEARANCE	GRADE	RECOMMENDED APPLICATION	PROPERTIES
<b>M/S. THE KERALA MINERALS AND METALS LTD.</b>				
KEMOX RC 822	White Powder	Rutile	Ceramic Application (Vitrified Tiles) Exterior Applications and powder coatings. Water and Solvents based paints, decorative and Industrial Coatings	High durability and chalk resistance excellent gloss and tint retention and good dispersibility
<b>M/S. TRAVANCORE TITANIUM PRODUCTS LTD.</b>				
AJANTOX-ISI	White Powder	Anatase	Ceramic Application (Vitrified Tiles) Paints, Paper, Plastics, Linoleum, Rubber, Leather Finishes, Soaps and Cosmetics.	High Brightness, tinting strength, good color and excellent dispersion characteristics in both aqueous and non-aqueous media
<b>M/S. TRONOX PIGMENTS LTD.</b>				
TRONOX CR 828	White Powder	Rutile	Ceramic Application (Vitrified Tiles) Interior and Exterior Industrial Coatings, Maintenance Coatings, Interior and Exterior Architectural Coatings and solvents and water based coatings	High optical properties, excellent durability, High gloss and high tint strength.
<b>IMPORTED</b>				
EUROXIDE	White Powder	Anatase	Ceramic Application (Vitrified Tiles) Paints, Paper, Plastics, Linoleum, Rubber, Leather Finishes, Soaps and Cosmetics	High Brightness, tinting strength, good color and excellent dispersion characteristics in both aqueous and non-aqueous media

### DISPERSING AGENT

GRADE	APPEARANCE	PROPERTIES
<b>M/S. AKZO NOBLE INDIA PVT LTD</b>		
ALCOSPERCE 645	Liquid	Dispersant & Viscosity Stabilizer for clay slurries particularly for Ceramic applications. (VITRIFIED TILES)